



INFORMACJA O PRODUKTACH - NICI DO HAFTU

PRODUKT	MATERIAŁ	GRUBOŚCI NICI		KOLORY	INSTRUKCJE PRANIA			ÖKOTEX	NAWOJE
		Nm	dtex		Pranie	Chlorowanie	Pranie chemiczne		
SULKY 40	100% CV	75/2	133/2	390	95°C	nie	tak	tak	1,000m, 5,000m
POLY 40	100% PES	80/2	125/2	300	95°C	tak	tak	tak	1,000m, 5,000m
POLY 60	100% PES	128/2	78/2	54	95°C	tak	tak	tak	1,500m
POLY FIRE	100% PES	80/2	125/2	27	95°C	tak	tak	tak	1,000m
POLY FLASH	100% PES	56/2	180/2	23	95°C	tak	tak	tak	1.000m
METY 7/2	51% PA 48% PES 1% metal	66	152	8	60°C	nie	tak	tak	1,000m, 5,000m
METY 5/2	59% PA 40% PES 1% metal	49	206	30	60°C	nie	tak	colour strip 2 tak	1,000m, 5,000m
COTTY 30	100% CO	50/2	200/2	182	95°C	tak	tak	tak	500m, 5,000m
COTTY 12	100% CO	30/2	330/2	117	95°C	tak	tak	tak	2.500m
FILAINE 12	100% acrylic	34/2	300/2	129	60°C	nie	tak	tak	1,000m
FLUOR FLUOR	50% PES	69/2	145/2	1	30°C	nie	tak	tak	1,000m
GLOWY GLOWY	50% PES 50% PP	69/2	145/2	7	30°C	nie	tak	tak	1,000m
MONO	100% PES	90/1	110/1	2	60°C	nie	tak	tak	22.500m; 500m
GLITTER	60% PES , 40% PE	75/1	133/1	24	60°C	nie	tak	nie	6.000m
REFLEX CRY	100% PA	250	12	1	40°C	nie	tak	tak	500m
REFLEX CRY	100% PA	200	30	1	40°C	nie	tak	tak	500m